



A DIVISION OF DAKOTA FLUID POWER, INC.

X SERIES BREATHER

Model	Check Valve PSI In/out	Height	Diameter	Mounting	Silica Gel	Maximum Absorption Capacity	Maximum Air Flow	Maximum Reservoir Fluid Flow	Type of Medium	Cartridge
X-100	0.3 0.3	6.25 in 15.9 cm	3.25 in 8.3 cm	1/2" FNPT	0.8 lbs 0.4 kg	4.91 fl oz 145 mL	10 cfm	75 gpm	100 % Silica Gel	L-143
X-101	0.1 2.0	7 in 17.8 cm	5 in 12.7 cm	1" slip fit	1.4 lbs 0.6 kg	8.6 fl oz 254 mL	20 cfm	150 gpm	100 % Silica Gel	A-341
X-102	0.1 2.0	10 in 25.4 cm	5 in 12.7 cm	1" slip fit	2.7 lbs 1.2 kg	16.56 fl oz 489 mL	20 cfm	150 gpm	100 % Silica Gel	A-342
X-103	0.1 2.0	7 in 17.8 cm	5 in 12.7 cm	1" MNPT	1.4 lbs 0.6 kg	8.6 fl oz 254 mL	20 cfm	150 gpm	100 % Silica Gel	A-345
X-105	0.1 2.0	10 in 25.4 cm	5 in 12.7 cm	1" MNPT	2.7 lbs 1.2 kg	16.56 fl oz 489 mL	20 cfm	150 gpm	100 % Silica Gel	A-346
X-121	0.1 2.0	7 in 17.8 cm	5 in 12.7 cm	2" MNPT	1.4 lbs 0.6 kg	8.6 fl oz 254 mL	20 cfm	150 gpm	100 % Silica Gel	A-343
X-122	0.1 2.0	10 in 25.4 cm	5 in 12.7 cm	2" MNPT	2.7 lbs 1.2 kg	16.56 fl oz 489 mL	20 cfm	150 gpm	100 % Silica Gel	A-344
X-501	0.1 0.1	7 in 17.8 cm	5 in 12.7 cm	1" slip fit	1.4 lbs 0.6 kg	8.6 fl oz 254 mL	20 cfm	150 gpm	100 % Silica Gel	A-341
X-502	0.1 0.1	10 in 25.4 cm	5 in 12.7 cm	1" slip fit	2.7 lbs 1.2 kg	16.56 fl oz 489 mL	20 cfm	150 gpm	100 % Silica Gel	A-342
X-503	0.1 0.1	7 in 17.8 cm	5 in 12.7 cm	1" MNPT	1.4 lbs 0.6 kg	8.6 fl oz 254 mL	20 cfm	150 gpm	100 % Silica Gel	A-345
X-505	0.1 0.1	10 in 25.4 cm	5 in 12.7 cm	1" MNPT	2.7 lbs 1.2 kg	16.56 fl oz 489 mL	20 cfm	150 gpm	100 % Silica Gel	A-346
X-521	0.1 0.1	7 in 17.8 cm	5 in 12.7 cm	2" MNPT	1.4 lbs 0.6 kg	8.6 fl oz 254 mL	20 cfm	150 gpm	100 % Silica Gel	A-343
X-522	0.1 0.1	10 in 25.4 cm	5 in 12.7 cm	2" MNPT	2.7 lbs 1.2 kg	16.56 fl oz 489 mL	20 cfm	150 gpm	100 % Silica Gel	A-344

3620 North Lewis Ave., Sioux Falls, SD 57104 | 888.925.8882 | y2kfiltration.com